



TECHNICAL DATA SHEET

C5 0W-20 OV LS

Fully Synthetic Low SAPS Engine Oil

Product code: FPOZ

Product Description:

C5 0W-20 OV LS is a new generation fully synthetic, low SAPS, fuel economy engine oil designed for use in a variety of modern petrol and diesel engine applications. It provides Low Speed Pre-Ignition (LSPI) protection and delivers significant levels of fuel economy in the latest OEM tests. C5 0W-20 OV LS is an ideal choice in hot running engines where its prevention of deposits keeps turbochargers in optimum condition and its carefully controlled SAPS levels protect after-treatment systems including petrol particulate filters.

Benefits:

- Low speed pre-ignition prevention
- Excellent fuel efficiency
- Ensures consistent lubricant performance over extended drain intervals
- Compatible with petrol particulate filters
- Outstanding turbocharger protection

Applications:

C5 0W-20 OV LS is recommended for many modern Vauxhall/Opel models as well as a number of newer BMW and Mercedes-Benz passenger cars plus select Jaguar Land Rover vehicles. It is also an ideal choice for service fill applications in many models produced by Asian manufacturers including Hyundai, Kia and Toyota.

Product Specification:

ACEA	C5, C6
API	API SQ, SQ-RC, SP, SP-RC
ILSAC	ILSAC GF-7A, GF-6A
BMW	Longlife-17 FE+, Longlife-14 FE+
Mercedes-Benz	MB 229.72, MB 229.71
Opel/Vauxhall	OV 040 1547-A20
Jaguar Land Rover	STJLR.03.5006
Ford	WSS-M2C947-B1, WSS-M2C962-A1, WSS-M2C954-A1
Fiat	9.55535-GSX
Volvo	VCC C6SP
Chrysler	MS-12145



TECHNICAL DATA SHEET

Typical Test Data:

Appearance	Clear & Bright
Density @ 15°C	0.840
Kinematic Viscosity @ 100°C (cSt)	8.17
Kinematic Viscosity @ 40°C (cSt)	42.0
Viscosity Index	173
Pour Point (°C)	-48
TBN (mg KOH/g)	7.9

Health & Safety:

Please refer to the safety data sheet, a copy of which is freely available to all of our customers.